ZOONLON CRAWLER SCISSOR LIFTS

ZS0612C

Comply with CE Standard



High Performance

- ► Rubber crawler for small ground pressure and great obstacle crossing ability
- ▶ Pivot steering with good maneuverability
- ► Simple single joystick control for steering and walking
- ► Click-to-level, simple to operate

Cost-Effectiveness

- ► Knuckles lubrication-free and maintenance-free
- ▶ AC motor full lifecycle maintenance-free
- ▶ Drawler battery tray, easy to maintain
- ▶ Emergency lifting arm, easy to service

Intelligent Connectivity

 Remote monitoring and rental system, easy to acquire machine info, efficient to run fleet



Standard Features

Proportional controls	Hour meter	
All motion alarm	Extension deck (unidirectional)	
Fold-down handrails	Charging protection system	
Flashing beacon	Scissor maintenance prop	
Self-closing entry gate	Forklift pockets	
Load sensing system	AC power to platform	

Accessories & Options

- Platform work lights
- ► Airline to platform
- ▶ Tool tray
- ▶ Anti-collision device





MAIN SPECS OF CRAWLER SCISSOR LIFTS ZS0612C

Comply with CE Standard

Model	ZS0612C		
	Imperial	Metric	
Size			
Work Height	25ft 7in	7.8m	
A Platform Height-Elevated	19ft	5.8m	
B Platform Height-Stowed	3ft 8in	1.13m	
C Platform Length	5ft 5in	1.65m	
D Platform Width	2ft 5in	0.74m	
Platform Extension	2ft 11in	0.9m	
E Overall Height (Rails Up)	7ft 5in	2.27m	
Overall Height (Rails Down)	6ft 2in	1.88m	
F Overall Length	7ft 2in	2.19m	
G Overall Width	3ft 9in	1.15m	
H Ground Clearance	3in	0.08m	
Performance			
Platform Capacity	510lb	230kg	
Capacity on Deck Extension	250lb	113kg	
Max. Number of Workers	2 (outdoor)		
Drive Speed (Stowed)	1.25mph	2km/h	
Drive Speed (Raised)	0km/h	0km/h	
Turning Radius	0in	0m	
Drive Motor	24V/2×2KW		
Up/Down Time	20/24s		
Gradeability	30%(17°)		
Max. Working Slope (Lateral/Vertical)	12°/7°		
Drive	Rear Wheels		
Brake	Rear Wheels		
Power			
Battery	4×12V/240Ah		
Charger	24V/30A		
Weight			
Gross	4012lb	1820kg	





